

Oneoil Plus

SAE 0W-20 Full Synthetic Motor Oil
API SN, API SN ILSAC GF-6A, GF-5

Product Description

Oneoil Plus SAE 0W-20 is a premium full synthetic motor oil manufactured for use in modern gasoline engines which require ILSAC GF-6A, API SP, API SN Plus, or API SN performance.

This oil is formulated with synthetic base oil and a premium performance additive package which is specially formulated to protect high compression gasoline direct injection engines delivering superior oxidative stability, deposit control, low speed pre-ignition mitigation and timing chain wear protection.

Typical Properties*

SAE J300 Viscosity Grade	0W-20
Appearance, Visual	Amber, Transparent, Liquid
Viscosity @ 40°C, cSt, ASTM D445	44.55
Viscosity @ 100°C, cSt, ASTM D445	8.3
Viscosity Index, ASTM D2270	165
CCS Apparent Viscosity, cP, ASTM D5293	5,400@-35°C
MRV Apparent Viscosity, cP, ASTM D4684	22,000@-40°C
Flash Point, °C, ASTM D92	210
Pour Point, °C, ASTM D97	-47

*The values shown are typical of current production. Some are controlled in the manufacturing process, while others are not. All of them may vary within tolerable ranges

Exceeds Performance Requirements

API SP with Resource Conserving, API SN Plus, API SN
ILSAC GF-6A, GF-5
GM dexos1™ Gen 2
Chrysler MS6395
Ford WSS-M2C947-A (0W-20)